



Cca

APPLICATION

The TOPSOLAR[®] PV H1Z2Z2-K cable, which is TÜV certified according to EN 50618 and AENOR certified according to IEC 62930, it is suitable for both fixed and mobile solar installations (solar farms, rooftop solar installations and floating plants).

It is a highly flexible cable compatible with all major connectors and specially designed for the connection of photovoltaic panels.

This versatile single-conductor cable is designed to meet the varying needs of the solar industry.

Suitable for wet, damp and humid locations.

- Solar PV installations string cable.

CONSTRUCTION

Conductor

Electrolytic annealed tinned copper, class 5 (flexible) according to IEC 60228 and EN 60228.

Insulation

Halogen free cross-linked rubber according to table B1 in Annex B of EN 50618 and IEC 62930.

Outer sheath

Halogen free cross-linked flexible rubber according to table B1 in Annex B of EN 50618 and IEC 62930.

Red or black colour.

CHARACTERISTICS

 **Electrical performance**
Low voltage: 1,5 (1,8) kV DC.
1,0/1,0 kV AC.

 **Thermal performance**
Maximum conductor temperature: 90°C (120°C during 20.000 h).
Maximum short-circuit temperature: 250°C (max. 5 s).
Minimum service temperature: -40°C (fixed and protected installations).

 **Fire performance**
Flame non-propagation according to EN 60332-1-2 / IEC 60332-1-2.
Fire non-propagation according to EN 50399.
Reaction to fire CPR: C_{ca}-s1b, d2, a1 according to EN 50575.
Low smoke halogen free according to EN 60754-1 / IEC 60754-1.
Low corrosive gases emission according to EN 60754-2 / IEC 60754-2.
Low smoke emission according to EN 61034 / IEC 61034:
Light transmittance > 60%.

 **Mechanical performance**
Minimum bending radius:
4x cable diameter (cable diameter ≤ 8 mm)
5x cable diameter (8 < cable diameter ≤ 12 mm)
6x cable diameter (cable diameter > 12 mm).
Impact resistance: AG2 Medium severity.

 **Environmental performance**
Chemical & Oil resistance: Excellent.
Grease & mineral oils resistance: Excellent.
Ozone resistant according to EN 50618.
UV Resistant according to EN 50618 and IEC 62930.
Water resistance: AD7+ Immersion.
AD8 Submersion.

 **Installation conditions**
Open Air.
Buried.
In conduit.

STANDARDS / COMPLIANCE

 **According to**
EN 50618/ IEC 62930 / UTE C 32-502

 **Standards and approvals**
TÜV Rheinland (from 2.5 to 25mm² in Black and Red) / RETIE / AENOR/ RoHS / CE / UKCA

 **CPR (Construction Products Regulation)**
C_{ca}-s1b, d2, a1



Type Approved
Safety
Regular Production
Surveillance
www.tuv.com
ID 1111257811

