


Shenzhen Enmind Technology Co., Ltd.

Add.: 5th Floor, Block A, Defengsheng Building, No.41 Dabao Road, Bao'an District 23, Shenzhen 518101, China
Tel.: +86 755 23316007 Fax: +86 755 22276344

Brand			
Image			
Function/Model		EN-V7P	EN-V5 vet
Screen		4.3" color touch screen	4.3" color touch screen
IV set installation direction		Horizontal	Vertical
Infusion mode	ml/h mode (include time and rate)	●	●
	Body weight mode	●	●
	Drip mode	●	●
	Dose mode	-	-
	Ramp up/down mode	○	-
	Sequence mode	○	○
	Drug library mode	○	○
	Loading dose mode	○	-
	Body surface mode	-	-
	Piggyback mode	-	-
	Cascade mode	○	-
	Intermittent Mode	-	-
	Micro mode	●	●
Flow rate range		0.01-2000ml/h (min.step 0.01ml/h)	0.1-2000ml/h (min.step 0.1ml/h)
WIFI		○	○
KVO		0.01-5ml/h	0.1-5ml/h
Occlusion alarm level	4 Level or 12 Level (optional)		5 Level
	225-900mmHg/150-975mmHg		50-900mmHg
Single bubble level	7 Level		5 Level
	50-800μL		50-800μL
Drug library (maximum)		30/2000 (optional)	2000
History records(maximum)		5000	5000
Brand library (maxinum)		30	200
Waterproof level		IP24	IP44
Appearance size parameter (Unit: mm)		235*95*120	138*131.5*90
Running time (minimum)		9hours @ 25ml/h	10hours @ 25ml/h
Battery capacity		2600mAh	5200mAh
Weight (bare machine does not contain fastening clips, handles and other accessories)		1.6kg	1.45kg
Compatible with cage fixation		-	●
Compliance with EN1789		●	●

Remarks: ● means standard, ○ means optional, --means no such function;